

# MANGER PRECISION IN SOUND

April 2023

HI home audio









Туре	Passive 2-Way Floorstanding Speaker		
Impedance	4 Ohms		
Frequency Range	40 Hz – 40 kHz		
Crossover Frequency	360 Hz	RAL or NCS colors	- 40 400 00
Sensitivity	89 dB 1 W/1 m	(satin finish	€12.190,00
Max SPL	106 dB Peak		
Dimensions	44.8" x 10.6" x 8.4" (1139 x 270 x 214 mm)		
Weight	61.7 lbs (28 kg)	Standard veneers	
High + mid Manger® Sound	I Transducer, Bandwidth 80 Hz – 40 kHz, Rise Time 13µs	(satin finish)	€12.790,00
Bass 8" Custom made C	arbon Fiber-Paper Sandwich Design, 42mm Voice Coil ø	(satin iiiisii)	
Enclosure	closed		
Rec. power	50 – 200 W		
Connectors	Bi-Wiring – WBT plasmaprotect nextgenTM Cu	Ultra High-Gloss	€14.260,00
Devialet SAM® Processing	available	(RAL and NCS colors)	€ 14.200,00
Finish	customized - colors, veneer or UltraHigh Gloss		
LINN Space Optimisation	listed in LINN database		
LINN Exakt Filter	listed in LINN database - contact us for an access link		



# **P2**

Туре	Passive 2-Way Floorstanding Speaker		
Impedance	8 Ohms		
Frequency range	30 Hz – 40 kHz		
Crossover frequency	340 Hz	RAL or NCS colors	
Sensitivity	89 dB 1 W/1 m	(satin finish	€14.690,00
Maximum SPL	112 dB Peak		
Dimensions (H×W×D)	1139 x 270 x 214 mm		
Weight	32 kg	Chandand	
High + Mid	Manger® Sound Transducer	Standard veneers (satin finish)	€15.490,00
Bass	8" patented Carbon fiber foam membrane, Sandwich layer design	(Satin Innsii)	ŕ
Enclosure	closed with two passive radiators		
ec. power	50 – 200 W		
Connectors	Bi-Wiring – WBT plasmaprotect nextgenTM Cu	Ultra High-Gloss	€1 <b>6.750,00</b>
Devialet SAM® Proces	ssing available	(RAL and NCS colors)	€ 10.750,00
Finish	customized - all colors, veneer or UltraHigh Gloss		
LINN Space Optimisat	ion listed in LINN database		
LINN Exakt Filter	listed in LINN database		









Туре	Passive 2-Way Compact Speaker		
Impedance	4 Ohms		
Frequency Range	40 Hz – 40 kHz		
Crossover Frequency	360 Hz	RAL or NCS colors	
Sensitivity	89 dB 1 W/1 m	(satin finish	€9.490,00
Max SPL	106 dB Peak		
Dimensions	21.0" x 10.6" x 14.3" (534 x 270 x 364 mm)		
Weight	57.3 lbs (26 kg)	Chan dand	
High + Mid	Manger® Sound Transducer	Standard veneers (satin finish)	€10.130,00
Bass 8" Custom made Car	bon Fiber-Paper Sandwich Design, 42mm Voice coil ø	(satin milsii)	ŕ
Enclosure	closed		
Rec. power	50 – 200 W		
Connectors	Bi-Wiring – WBT plasmaprotect nextgenTM Cu	Ultra High-Gloss	€11.160,00
Finish	customized - all colors, veneer or UltraHigh Gloss	(RAL and NCS colors)	€11.100,00
Devialet - SAM® Processing	available		
LINN Space Optimisation	listed in LINN database		
LINN Exakt Filter	listed - ask us for LINN database access		



# **Z1 Stand**

Material: Aluminum anodized

Dimensions: 549 (Height) x 270 (top plate) x 465 (foot plate) mm

Weight: 14 kg

Aluminum anodized or black €2.580,00







#### **W1**

Type
Impedance
Frequency Range
High pass frequency
Sensitivity
Max SPL
Dimensions
Angle
Weight

Rec. power Connectors Wall mounting Finish Applications Passive 1-Way On-Wall Speaker 8 Ohms 150 Hz – 40 kHz

10.4" x 17.2" x 2.8"/5.4" [264 x 436 x 71/136 mm]

Pure on-wall stereo or full/part immersive audio system

150 Hz RAL or NCS colors 89 dB 1 W/1 m (satin finish 106 dB Peak

tin finish €5.790,00

17.6 lbs (8 kg)

Manger® Sound Transducer

50 - 200 W


Single-Wiring Terminal with 3 cable channels (Left/Right/Center)


Wall fixing plate including drilling template

Ultra High-Gloss

(RAL and NCS colors)

€7.640,00





#### **i**1

Passive 1-way in-wall speaker Driver:

- HF: MSW (120 Hz - 40 kHz), rise time 13 μs

all colors or UltraHigh Gloss

Cabinet: Closed

Freq. response: 120 Hz - 40 kHz (optional without crossover)

Impedance: 8 ? Sensitivity: 90 dB (1 W/ 1 m)

Connectors: 1 pair binding-post

Dimensions (H x W x D): 390 x 435 x 120 mm

Weight: 11,7 kg

#### **i2**

Same of i1, but in cell €5.170,00

€5.990.00







#### **C1**

Type Frequency range	Active 2-Way System 30 Hz - 40 kHz		
Crossover frequency	330 Hz		
Max. SPL	110 dB Peak	RAL or NCS colors	- 47 400 00
Dimensions	19.5"x10.6"x16.7" (495 x 270 x 424 mm)	(satin finish	€15.490,00
Weight	66.1 lbs (30 kg)		
Max. Power Output LF	250 W @ 8 Ohms Class AB		
Max. Power Output HF	180 W ଜ 8 Ohms Class AB	Standard veneers	
Power Bandwidth HF	250 kHz (-3 dB)	(satin finish)	€16.540,00
Input Sensitivity	6 dBu (1.55 V) or 0 dBu	(Satin Illisii)	
Input Impedance	10 k0hms		
Input	XLR-3 (balanced)		
LINN Space Optimisation	listed in LINN database	Ultra High-Gloss (RAL and NCS colors)	€17.370,00



### LF Module

Extra passive woofer module (max. SPL +6dB) Will be connected to c1 and switched parallel to built-in woofer no extra-amplifier required Dimensions (H x W x D):  $264 \times 270 \times 343 \text{ mm}$ 

Weight: 11 kg RAL or NCS colors (satin finish €3.690,00

#### C1 Stand

Height: 620 mm Dimensions Standard veneers (satin finish) €4.549,00

Weight: 14 kg

Price: Same of Z1 Stand

Ultra High-Gloss
(RAL and NCS colors)

€5.900,00

#### C1 Lift

Height: adjustable between 780 mm - 1080 mm Aluminum anodized

Price on request







#### S1 Type

LINN Space Optimisation LINN Exakt Filter

.,,,,,	i assive z viaj compact opeaker		
Impedance	4 Ohms		
Frequency Ra	ange 40 Hz – 40 kHz		
Crossover Fr	requency 360 Hz	RAL or NCS colors	
Sensitivity	89 dB 1 W/1 m	(satin finish	€19.200,00
Max SPL	106 dB Peak	·	
<b>Dimensions</b>	21.0" x 10.6" x 14.3" (534 x 270 x 364 mm)		
Weight	57.3 lbs (26 kg)	C	
High + Mid	Manger® Sound Transducer	Standard veneers (satin finish)	€19.99000
Bass	8" Custom made Carbon Fiber-Paper Sandwich Design, 42mm Voice coil ø	(Satin iiiiiSii)	
Enclosure	closed		
Rec. power	50 – 200 W		
Connectors	Bi-Wiring – WBT plasmaprotect nextgenTM Cu	Ultra High-Gloss	e31 300 00
Finish	customized - all colors, veneer or UltraHigh Gloss	(RAL and NCS colors)	€21.290,00
Devialet - SA	M® Processing available		

listed - ask us for LINN database access

Passive 2-Way Compact Speaker

listed in LINN database







# Manger® Holoprofile

Invented and patented sound guide
Shaped high-attenuation special thermoplastic, fixed with high-attenuation PU plastic mounting points: acoustically decoupling double-sided adhesive pads.

€465,00



# Manger® cone feet

High damping POM plastic cone feet ( H 14mm x  $\emptyset$ 18mm) with M8 thread 1 set = 8 pcs.

(comes standard with all floor standing speaker models)

Black €130,00







# Manger® CD

Music Sampler - 15 tracks, 16 bit/44.1kHz

"Please give my compliments to the person who compiled your demonstration CD, it's the best in business"

Flemming E. Rasmussen, Gryphon Audio

€24.90,00



# Manger® Double LP

Music Sampler - 15 tracks, 2 LPs, 180 grams - manufactured with virgin vinyl

"These records can tell a lot about the quality of any analogue playback chain.

Thank you to Manger for providing such a useful tool!"

Hartmut Quaschik - www.tnt-audio.com

€54.90,00

# MANGER PRECISION IN SOUND





#### Plays perfectly with Devialet and Linn

To bring powerful technology to your passive Manger speaker, the p1 and p2 seamlessly work with both Linn's Exakt and Devialet's SAM Processing.

In combination with Linn Exakt, your passive speaker is enhanced with powerful software and performance features, becoming an active speaker.

